



Washer extractors

High Spin washer extractors TP

HIGH SPIN WASHER EXTRACTOR, LA-45 TP E

<u>DIMENSIONS</u>		<u>Article</u>	<u>Packed</u>
Length	mm	1.478,00	1.540,00
Depth	mm	1.444,00	1.580,00
Height	mm	1.905,00	1.970,00
Weigth	Kg	1.350,00	1.420,00
Volumen	m3		4,79
<u>ELECTRICITY</u>			
<u>Electric power</u>			31,30
230V -1+N	KW		NO
230V - III		3x25+T-80A	
400V - III+N		4x10+T-50A	
<u>WATER</u>			
Water consumption (lit/h)			420,00
Pressure (Kg/cm2)			2 - 4
<u>GAS</u>			
Not used			
<u>STEAM</u>			
Not used			
<u>AIR</u>			
Not used			
<u>LEVEL SOUND</u>			
	(dB)		70,00

HIGH SPIN WASHER EXTRACTOR, LA-45 TP E

Made of stainless steel.

Capacity: 50 kg (1:9) or 45 kg (1:10).

Microprocessor "Touch Plus Control" with display.

26 pre-set programs (4 economic programs).

Possibility of programming, export and import programs through USB memory, without limite.

"WASH CONTROL" management software included.

Digital sequence display.

8 signals for automatic liquid dosing, programmable in time and delay.

Possibility to install an automatic detergent doser on the rear of the machine.

Detergent dispenser with 4 compartments (pre-wash, wash, bleachers and softeners).

Water levels completely modifiable.

3 water inlets (Hot water, Cold water, Soft water).

WET CLEANING SYSTEM:

-Water levels completely modifiable.

-Possible manual dosing for evey 8 signals during the cycle.

-Minimum washing speed: 15 r.p.m.

-Minimum thyrhm ON-OFF: 1 second.

Safety door system.

Drum diameter: 918 mm.

DeePTH drum: 720 mm.

Door diameter: 560 mm.

Spin speed: 850 r.p.m.

G Factor: 350.

These machines have electronic control of imbalance with frequency variator, that detects the load uncentered before spinning.

Wash and spin speeds are configurable.

No need to anchorage to the floor.

Second drain option.

Easy to attach automatic doser dispenser at rear of machine.

Water consumption in program n° 2 60°: 420 litres.

Heating system: Electric.

Elements heating power: 24 kW.

Total power: 31,3 kW.

Dimensions: 1.478 x 1.444 x 1.905 mm.

Connections points	X	Y	Z	Diameter	Information
ELECTRICITY	770	0	1.650		0
DRAIN	765	0	410	3"	
DRAIN	545	0	410	3"	
COLD WATER	735	0	1.515	1"	
SOFT COLD WATER	435	0	1.515	1"	
HOT WATER	585	0	1.515	1"	

