

PB
SERIES

PB IRONERS

POWERING DETAILS

PB/PBP5119
PB/PBP5125
PB/PBP5132
PB3215
PB3221




GIRBAU

PB IRONERS

POWERING DETAILS

PB/PBP5119
PB/PBP5125
PB/PBP5132



PB3215
PB3221




THE EXCELLENCE IS IN THE DETAIL

Let your customers experience excellence in all its details and enjoy the benefits of professional ironing in your business.

- +** **QUALITY**
Girbau's exclusive kinematic strap tension system and Care Touch Roll ensure a quality finish.
- +** **PRODUCTIVITY**
The efficiency of the PB ironers makes it possible to process garments directly from HS Series high speed washing machines, while guiding the operator during the ironing process.
- +** **SAFETY**
The hand-guard protection system ensures operator safety. A double sensor monitors the active and rest position with an initial check at each start-up.
- G** **EXPERIENCE**
We pass on the know-how we acquire to our clients when defining the laundry project suited to their needs, and with the continuous advice and training of the Girbau Laundry Tips service.
This is how we achieve Easy & Best Solutions.

ERGONOMICS

The position and width of the feeding belt where the linen is positioned, and good foot access under the belt make for effortless ironing operations, allowing the operator to maintain a comfortable and natural position while working, and thus avoid unnecessary effort.



WE TAKE GREAT CARE OVER THE DETAILS

Feel the crisp freshly ironed sheets on your skin, lay in bed wrapped in a comfy quilt, set out a napkin and observe the geometry of its folds, or see how a perfect tablecloth makes a dinner much more special. Can anyone doubt the power of details? Does anyone doubt how every detail in each article of linen can become a sensation?

Girbau's ironers seduce with their details, with the finish they give to the linen. This is why we design our equipment down to the last detail, as befits equipment destined to become every laundry's badge of honour.

Because we want our customers to feel the essence of the detail.

GIRBAU

FLEXIBILITY

The main objective of the PB Series ironers is to aid the ironing process in laundries where space and production make this a critical process. The flexibility of this product reveals itself in its multiple configurations and heating options.

HEATING OPTIONS

ELECTRIC

It is not synonymous with high consumption, and is essential for laundries where there are no other energy supplies.

STEAM




Steam continues to be a requirement for many laundries and is a system that delivers high performance, which is why it is also available for the PB Series.

GAS


A clean and highly efficient system that requires the minimum of maintenance. Two types of burner.

Atmospheric, standard burner.


Radiant, an enriched mixture that provides greater power and efficiency.



SETTINGS




Roll diameter:	Useful input length:
320mm	1,500mm
510mm	1,900mm
	2,100mm
	2,500mm
	3,200mm





EVEN IRONING



A PATENT THAT MAKES THE DIFFERENCE

The **Kinematic tensioning system** patented by Girbau is one of the key factors in explaining the quality of the finish obtained in PB ironers.

This system is based on a permanent balance of tensions and weights between different rolls that achieves permanent tensioning of the straps. The system uses the movement of the straps along the rolls to rebalance these in order to maintain an even tension and achieve a professional finish.



CARE TOUCH ROLL

A roll with a chrome surface coating that achieves excellent ironing quality, extends the life of the fabric, and is also highly resistant to corrosion even after periods of inactivity.

The **angle of contact** of the linen with the roll is **270°**, making it possible to work at high speed (up to 11 and 15 m/min, depending on the model).






GIRBAU

DESIGNED TO LAST


+ HARD-WEARING The ironer's safety covers are metal, and therefore more hard-wearing. The roll is made of machined steel with mirror polishing and chrome plating. The bearings are lubricated with grease that is permanently temperature resistant.

+ RELIABILITY The gear motor-inverter assembly provides a secure transmission, more speed ranges and less wear and tear.

+ ACCESSIBILITY All the machine's parts are designed to be extremely accessible and easy to maintain. The lint filter is easy to clean. The metal side covers make for easy maintenance operations.



▲ Moisture extracted by suction



▲ Filter



▲ Safety covers



FEEDING AND FOLDING





FEEDING

With the PB series, 1, 2 or 4 lanes can be fed simultaneously, for all kinds of linen (sheets, table linen and small items such as napkins and pillowcases).

FOLDING

The **PBP models** incorporate a **1-lane folder** using a photocell system that calculates the total length of the item and adjusts the primary folding.

In **automatic mode** it adapts to all kinds of article without needing to change the program or interrupt the process.



▲ Up to 14 primary folds.

In **manual mode** the operator sets the length of the article and the controller determines the number of folds and their length. In **advanced mode** the operator sets the length of the article and selects the number of folds desired.



ASSISTING IRONING TO IMPROVE PRODUCTIVITY

Understanding ironing as a process and not as a simple activity is what makes PB ironers different. We have analysed every step of the process, and for each step we have looked for mechanisms that help to make the ironing operation more cost-effective, productive, comfortable and safe.

In PB ironers you will find the best assistant for improving the productivity of your laundry.

IRONING ENHANCEMENT

CONTROL INTELI CONCEPT

Programming and controlling the PB Series ironer is straightforward and intuitive. A system of easily understood icons indicates the program, the real and the programmed temperature, the speed and the length of the article, in addition to advising the operator on the most optimum and productive operating mode.



AUTOSPEED

The Autospeed system automatically adjusts the ironing speed depending on the type of linen and the degree of dampness. With Autospeed it is possible to maintain an even and stable temperature. The sensors capture precise and reliable information.




OPTIFEED



The control display indicates the feeding area with the highest temperature in real-time, in order to take the fullest advantage of the heat energy and increase productivity. The system is designed to guide the operator during the ironing process, and adapts to the type of garment and conditions.



← PB32



▼ PB51



PB FLATWORK IRONERS




PO1335 19/05

MODEL			PB3215	PB3221	PB5119 PBP5119	PB5125 PBP5125	PB5132 PBP5132	
Power	Roller motor (50 Hz)	kW	0,25 (0,37 High speed)		0,55 (1,1 High speed)			
	Extraction motor (50Hz)	kW	0,30		0,55			
Heating	Electric	Electric heating power **	kW	16,6	23,4	38,0	49,7	63,5
		Evaporation	l/h (c.f.h.)	15,0 (0,5)	20,0 (0,7)	30,0 (1,1)	40,0 (1,4)	50,0 (1,8)
	Gas	Gas power Atmospheric Burner	kW (B.T.U./h)Hi*	22,3 (76.091)	30,5 (104.070)	39,9 (136.144)	51,5 (175.725)	69,6 (237.485)
		Evaporation	l/h (c.f.h.)	15,0 (0,5)	20,0 (0,7)	30,0 (1,1)	40,0 (1,4)	60,0 (2,1)
		Gas power Premix Burner	kW (B.T.U./h)Hi*	25,0 (85.304)	33,3 (113.624)	46,9 (160.029)	60,1 (205.070)	80,9 (276.042)
	Steam	Steam power	kW (B.T.U./h)	-		48,8 (166.513)	65,0 (221.789)	81,4 (277.748)
		Evaporation	l/h (c.f.h.)	-		42,0 (1,5)	56,0 (2)	70,0 (2,5)
Voltage	Electric	3Ph 50Hz (V)	200-220-230-240-380-400-415					
		3Ph 60Hz (V)	200-208-220-240-380-415					
	Gas-Steam	2Ph 50Hz (V)	380-400-415					
		2Ph 60Hz (V)	415-440-480					
		1Ph 50Hz (V)	200-220-230-240					
1Ph 60Hz (V)	200-208-220-240							
Options	Folder		-		PBP Model			
	Double photocell assembly (PBP only)		-		-	Yes		
	High Speed option		Yes (11m/min)		Yes (15m/min)			
Dimensions and weights	Cylinder diameter	mm (in.)	325 (12.8)		510 (20.1)			
	Useful length of cylinder	mm (in.)	1.540 (60.6)	2.120 (83.5)	1.900 (74.8)	2.530 (99.6)	3.165 (124.6)	
	Speed	m/min (ft/min)	1 - 5 (3-16)		1 - 9 (3-30)			
	High Speed option	m/min (ft/min)	1 - 11 (3-36)		1 - 15 (3-49)			
	Noise level	dB (A)	< 70					
	Net weight G - E	PB kg (lbs)	459 (1.012)	561 (1.237)	1.035 (2.282)	1.265 (2.788)	1.423 (3.137)	
		PBP kg (lbs)	-	-	1.132 (2.496)	1.392 (3.069)	1.586 (3.497)	
	Net weight V	PB kg (lbs)	-	-	1.145 (2.525)	1.375 (3.031)	1.533 (3.379)	
		PBP kg (lbs)	-	-	1.242 (2.739)	1.502 (3.312)	1.696 (3.739)	
	Gross weight G - E	PB kg (lbs)	617 (1.360)	740 (1.630)	1.285 (2.834)	1.560 (3.439)	1.758 (3.876)	
		PBP kg (lbs)	-	-	1.397 (3.080)	1.712 (3.775)	1.946 (4.290)	
	Gross weight V	PB kg (lbs)	-	-	1.395 (3.076)	1.670 (3.681)	1.868 (4.118)	
		PBP kg (lbs)	-	-	1.507 (3.323)	1.822 (4.017)	2.056 (4.533)	
Height H	mm (in.)	1.416 (55.7)		1.630 (64.2)				
Width L	mm (in.)	2.313 (91.1)	2.895 (114)	2.837 (111.7)	3.470 (136,6)	4.103 (161.5)		
Depth P	mm (in.)	872 (34.3)		1.173 (46.2)				

* Hi - Lower heating value / ** Output calculated at 400V III

GIRBAU S.A. reserves the right to change design and/or specification without notice



BRANCHES

Argentina - Buenos Aires - Tel. +54-1 149017600 - girbauargentina@girbau.com
 Australia - Sydney - Tel. +61 2 96755860 - sales.australia@girbau.com
 Brazil - Sao Paulo - Tel. +55 11-29820446 - girbaudobrasil@girbau.com
 China - Shanghai & Hongkong - Tel. +86-21-5713 1103 - info.china@girbau.com
 Cuba - La Habana - Tel. (+53-7) 8662071 al 73 - girbau@girbau.co.cu
 Dominican Rep. - Punta Cana - Tel. +1 809-959-0615 - infodominicana@girbau.com
 France - Grésy sur Aix - Tel. +33 456 574 030 - infofrance@girbau.com
 Germany - Ratingen - Tel. +49 2102 9934619 - girbaugermany@girbau.com
 Italy - Marcon (VE) - Tel. +39 0418654330 - infoitaly@girbau.com
 Mexico - Cancún - T. +52 998 688 6336 - info.mexico@girbau.com
 Portugal - Porto - Tel. +351 22 3758909 - vendasportugal@girbau.com
 U.A.E. - Dubai - Tel. +971 4-8839951 - sales.gme@girbau.com
 U.K. - Hitchin - Tel. +44(0)-1462 427780 - info.uk@girbau.com
 U.S.A. - Oshkosh, WI & Los Angeles, Ca - Tel. +(920) 2318222 - info@cgilaundry.com

HEADQUARTERS

GIRBAU, S.A. Ctra de Manlleu, km. 1 - 08500 Vic (Barcelona) Spain - girbau.com
 Tel. (+34) 93 886 2219 - sales@girbau.com

